

## New SP100VCBL Variable-Flow OEM Pumps

These low-cost peristaltic pumps are among the most compact, most powerful variable-flow pumps in the market. Flow rates are available from 0 to 40 ml/min. They adapt easily to almost any instrument application. Enjoy the benefits of peristaltic pumps in your fluid transfer application.

Select from 2 different Vdc motor speeds, three different tubing sizes and a variety of tubing materials. Tygon® A60G tubing offers the longest pump life, Silicone is the softest with higher flow rates. Viton® provides excellent chemical resistance. Modular power supplies and battery packs are available.

The pumpheads have ABS plastic housings, acetal rotor assembly with four stainless steel rollers. These heavy-duty, brushless Vdc motors are reversible and rated for continuous-duty. Silicone and Tygon® A60G pump systems are supplied with polypropylene fittings. Viton® systems are supplied with PVDF fittings. One year warranty.

**Installation Note:** These heavy-duty BLDC motors are rated for long-term continuous-duty applications.

### SPECIAL FEATURES

*Fluid only contacts the tubing  
Rated for continuous-duty  
Self-priming, run dry without damage  
Variable-flow 12Vdc motors  
Consistent metering capability*

### SPECIFICATIONS

	Tygon®, Viton®	Silicone
Max. Fluid Pressure:	30 psig (2 bar)	10 psig (0.7 bar)
Max. Suction Lift:		
0.8 and 1.6 mm ID	16-ft (4.8 m) H <sub>2</sub> O	16-ft (4.8 m) H <sub>2</sub> O
3.0 mmID	25-ft (7.5 m) H <sub>2</sub> O	25-ft (7.5 m) H <sub>2</sub> O
Flow Range:	See ordering table (page 2)	
Accuracy:	±2% full scale	
Repeatability:	±2% full scale	
Max. Fluid Temp.:	93°C (200°F)	
Duty Cycle:	Continuous; 20,000 hrs	
Operating Temp.:	0 to 50°C (32 to 122°F)	
Enclosure:	PVC	
Wetted parts:	Various tubing materials	
Power:	12Vdc; 150 to 800 mA (24Vdc models available)	
Dimensions (W x H x D):	100 x 100 x 132 mm; (4 x 4 x 5.2 in.)	
Shipping Wt:	1.4 kg (3 lbs)	

**Variable-flow  
Reversible  
Heavy-duty, BLDC motors**



*Compact, variable-flow  
SP100 Vdc BLDC pumps with  
optional remote control.*

### APPLICATIONS

*Chemical metering  
Reagent dispensing  
Chemical waste removal  
Analytical instruments  
Research & Development*

### SP100VCBL Max Flowrates (ml/min)

Motor RPM	Vdc	Amps	Tubing ID (mm)		
			3.0	1.6	0.8
200	12	800 mA	40	12	4
10	12	250 mA	1.9	0.54	0.09

Flow rates listed are nominal and will vary depending upon fluid viscosity and back pressure. Specifications listed are for Tygon A60G (formerly Norprene) tubing. Silicone flow rates are approx 10-20% higher. Viton flow rates slightly lower.

# SP100VCBL-Peri Pumps

## SP100VCBL Ordering Information – (Flow rates listed are for Tygon® A60G tubing; Silicone is 10-20%

<u>Flow Rate</u>	<u>Tubing</u>			<u>Pump Part No.</u>	
ml/min	ID	RPM Range	V-Flow,I/O	V-Flow,I/O/R	V-Flow,I/O/R,Rem
12Vdc Pumps - Variable-flow; up to 500 mA current draw; Select Tubing Material below.					
0 to 40	3.0 mm (1/8")				
0 to 12	1.6 mm (1/16")	0 to 200	SP10XV1-215A	SP10XV1R-215A	SP10XV3R-215A
0 to 4	0.8 mm (1/32")				
0 to 2	3.0 mm (1/8")				
0 to 0.6	1.6 mm (1/16")	0 to 10	SP10XV1-212A	SP10XV1R-212A	SP10XV3R-212A
0 to 0.2	0.8 mm (1/32")				

V-Flow=Variable-flow; I/O=On/Off Switch; I/O/R=On/Off/Reverse Switch; Rem=Remote Speed (0-5Vdc); Rem Start/Stop: Remote Direction.

Flow rates listed are nominal and will vary depending upon fluid viscosity and back pressure.

24 Vdc systems are available. Other motor rpms and special tubing options are available on special order. Call for details.

## Tubing Set Material Selection

Part No:	Description	Sizes Incl.(mm)	Fitting	Application Recommendations
SP101-980AF	Tygon® A60G	3, 1.6, 0.8 ID	PP	Longest flex life, Black, Good with Acids/Bases
SP101F-980AF	Tygon® A60F	3, 1.6, 0.8 ID	PP	Longest flex life, Beige, Food-Grade
SP104L-980AF	Tygon® LFL	3, 1.6 ID	PP	Long flex life, Clear, USP, FDA
SP100-980AF	Silicone	3, 1.6, 0.8 ID	PP	Good flex life, Translucent, General Purpose
SP100P-980AF	Tygon® 3350 (Sil)	3, 1.6 ID	PP	Good flex life, Translucent, USP, ultra smooth
SP104P-980AF	Tygon® F-4040	3, 1.6 ID	PP	Good flex life, Yellow Transl, Fuel/Lubricant
SP104X-980AF	Tygon® XL-60	3, 1.6 ID	PP	Good flex life Clear, General Purpose
SP101R-980AF	Tygon® Chemical	3, 1.6 ID	PP	Long flex life, Beige, Chem Resistant liner
SP102-980AF	Viton®	3, 1.6, 0.8 ID	PVDF	Good flex life, Black, FDA, Chem Resist-Organics

## VAC power supply

Convert these compact drives to VAC models with a compact power supply. 5.5 OD x 2.5mm ID (center + ) connector.

Order the optional power supply.

PS100.010 Power supply, 115Vac/12Vdc, 1A; US Std plug.

PS100.015E Power supply, 230Vac/12Vdc, 1A; Europ. plug.

Specifications subject to change.

APT Instruments provides no warranty on usage of pumps or life of tube. Immersion and life tests are recommended prior to use.

SmallPumps—TM Advanced Product Technology, LLC Viton—Reg TM DuPont Dow Elastomers LLC

Tygon—Reg TM Saint Gobain Performance Plastics Corp.

© Copyright 2009-17 Advanced Product Technology, LLC.

**For more information contact:**

**APT Instruments Div**

**Omaha, NE 68144 USA**

**877.324.5444 Toll-free**

**217.498.0342 \* 217.498.0352Fx**

**[www.aptinstruments.com](http://www.aptinstruments.com)**

**[sales@aptinstruments.com](mailto:sales@aptinstruments.com)**